

# GV-2408DC

4" Desktop Direct Thermal Label Printer



## Key Features

- 203.2mm (8") per second print speed for 203 dpi.
- Internally scalable TrueType font engine.
- Firmware emulates the following: TSPL, ZPL, ZPL II.
- Provides Windows utility, Android utility, Windows SDK, Android SDK and iOS SDK.
- Solutions for retail POS, shelf labeling, office applications and logistic.

POWERFUL | HIGH PERFORMANCE | AFFORDABLE

# 4" Desktop Direct Thermal Label Printer

| MODEL               | GV-2408DC   |
|---------------------|---|
| Printing method     | Direct Thermal  |
| Resolution          | 203DPI  |
| Print speed         | 203.2mm(8")/second  |
| Print width         | 104 mm(4.1")  |
| Interface           | · USB 2.0<br>· Internal Bluetooth 4.2 (Factory option)<br>· Internal Wi-Fi (Factory option)   |
| 1D Barcode          | Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Pleassy, PostCode, Telepen |
| 2D Barcode          | QR Code, Micro QR Code, PDF417, Micro PDF417, MaxiCode, Aztec Code, Data Matrix   |
| User Interface      | 1 power switch, 2 buttons (Feed & Pause)<br>2 LEDs (Online, Error)  |
| Sensors             | Head open sensor<br>Reflective sensor (Moveable), Transmissive sensor   |
| Label roll capacity | Max. 127mm (5")OD   |
| Printer language    | Compatible to TSPL, ZPL, ZPL II   |
| Media type          | Continuous, die-cut, black mark, fan-fold, notched (Outside wound)  |
| Dimension           | 245mm (L) *186mm (W) *178mm (H)   |
| Net weight          | 1.56kg  |
| Certification       | FCC, CE   |



## Application Industries



Healthcare



Shelf labeling



E-commerce



Retail



Logistic



Shopping Mall